

REEDEE.Co., Ltd.

PPF03-75AG Physical properties

Main features:

- * All-round coverage of car paint, isolation protection is long-lasting and effective
- * Prevent car paint scratches and prevent car paint from fading
- * Self-repair of corrosion and scratches, improve paint brightness
- Good weather resistance and aging resistance

Product structure:

 Self-healing
 8±2μm

 TPU
 150±5μm

 PSA
 30±3μm

 Release film
 92±3μm

Use layer thickness:188±10μm

Physical properties:

| | · 1 | <u>.</u> | 1 | |
|-------------------------------------|---------------------|--------------------------------------|--|--|
| Index | Unit | Range | Test Instrument | Testing Method |
| Thickness | mil | ≥7.5 | Mitutoyo H0530 Digital Dial Indicator | GBT/29061 |
| Elastic Modulus | Kgf/cm ² | ≤300 | Electronic tensile testing machine | ASTM D-882 |
| Coating breakage Elongation | % | ≥100% | Electronic tensile testing machine | STM D-882 |
| Initial Tack | N/in | 15≤F≤25 | Tension meter | FINAT3 |
| Sticky Force | N/in | 20≤F≤35 | Tension meter | FINAT3 |
| Water Transfer | 0 | >70,<90 | Water drop angle tester | GB/T 30693-2014 |
| Anti-fouling Properties | / | Slight residue | Chenguang MG-2110 marker pen | Apply with a marker and wipe with alcohol after drying |
| Scratch Resistance | / | no scratches | fine copper brush | 10 scratches with a fine copper brush with a load of 200g/cm2 |
| Repair Performance | S | ≤5 | Fine copper brush, hot water, baking gun | Scratch 10 times with a fine copper brush with a load of 200g/cm2, Repair with hot water or hot air around 70°C |
| Aging Resistance | / | △E≤2 No cracking or blistering | QUV Aging Tester | QUV (0.5W, 40°C, 360nm, 120 min 3200 hours |
| Anti-aging Oil Cleaning Performance | / | 2minutes without fog | Branded carburetor cleaner | The product is attached to the car paint cover and sprayed with cleaning agent |

• Note: The above are only reference values, not guaranteed values.

Office Address: Room 6-207, Longfeng Industrial Park, No. 1 Tianxi Road, Guanlan Street, Longhua District, Shenzhen TEL: 0755-23702112

Factory address: Jingheng Optoelectronics, Songling Industrial Zone, Sima Village, Changping Town, Dongguan City TEL: 0769-81188755/81188765